

## 1 . IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

**Product Name:** MOTORKOTE DIESEL STICTION REMOVER

**Recommended Use of the Chemical and Restriction on Use:**  
Cleans and removes build up on oil side of diesel injector.

**Details of Manufacturer or Importer:**

Verditure Trading Co. Pty Ltd  
52 Henderson Street  
Camp Hill QLD 4152

**Phone Number:** 07 3395 4705

**Emergency telephone number:** 1300 138 300

## 2 . HAZARDS IDENTIFICATION

**Hazardous Nature:**



GHS08 health hazard

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

H227 Combustible liquid.

**Label Elements**

**Signal Word** Danger

**Hazard Statements**

H227 Combustible liquid.

H319 Causes serious eye irritation.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

**Precautionary Statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash hands thoroughly after handling.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national regulations.

(Contd. on page 2)

Printing date 30.10.2013

Revision: 30.10.2013

**Product Name: MOTORKOTE DIESEL STICTION REMOVER**

(Contd. of page 1)

### 3 . COMPOSITION AND INFORMATION ON INGREDIENTS

**Chemical Characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Hazardous Components:**

64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic ☠ Carc. 1B, H350	88-98%
71-36-3	1-Butanol ☠ Flam. Liq. 3, H226; ☠ Eye Dam. 1, H318; ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-5%

### 4 . FIRST AID MEASURES

**Inhalation:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

**Skin Contact:**

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

**Eye Contact:**

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

**Ingestion:**

If swallowed, give large amounts of water. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Do not give anything by mouth to an unconscious person. Seek immediate medical attention.

**Information for Doctor**

**Symptoms Caused by Exposure:**

Inhalation: Irritation of nose, throat and respiratory tract.

Skin contact: Redness, dryness and irritation.

Eye contact: Redness, stinging and irritation.

Ingestion: Nausea, vomiting, dizziness, headache and blurred vision.

### 5 . FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:**

Regular foam, carbon dioxide and dry chemical. Do not use a direct stream of water on burning liquid; product will float and can be reignited on surface of water.

**Specific Hazards Arising from the Chemical:**

Material will not burn unless preheated.

Closed containers may explode when exposed to extreme heat. Use water spray to cool fire exposed containers.

A complex mixture of airborne solid, liquid, particulates, and gases will evolve when this material undergoes pyrolysis or combustion.

**Special Protective Equipment and Precautions for Fire Fighters:**

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing.

(Contd. on page 3)

**Product Name: MOTORKOTE DIESEL STICTION REMOVER**

(Contd. of page 2)

**6 . ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment and Emergency Procedures:**

Wear Safe Work Australia approved self-contained breathing apparatus and full protective clothing (for large spills). Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

**Environmental Precautions:**

In the event of a major spill, prevent spillage from entering drains or water courses.

**Methods and Materials for Containment and Cleaning Up:**

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools. Ensure adequate ventilation. Extinguish all sources of ignition. Flush area for trace residue.

**7 . HANDLING AND STORAGE**

**Precautions for Safe Handling:**

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

**Conditions for Safe Storage:**

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Protect from heat, sparks, open flames and other sources of ignition. Keep away from strong oxidising agents.

**8 . EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**Exposure Standards:**

Oil mist:

TWA: 5 mg/m<sup>3</sup>

**71-36-3 1-Butanol**

NES	TWA: 152* mg/m <sup>3</sup> , 50* ppm
	Sk;*Peak limitation

**Engineering Controls:**

Provide mechanical ventilation or other engineering controls to keep the airborne concentrations of vapour below occupational exposure standards.

**Personal Protective Equipment (PPE):**

**Respiratory Protection:**

Normally not needed in a well ventilated area. If workplace exposure limit is exceeded, a Safe Work Australia approved air supplied respirator is recommended. See Australian Standards AS/NZS 1715 and 1716 for more information.

**Skin Protection:**

Rubber, neoprene or vinyl gloves and protective clothing. See Australian Standards AS/NZS 2161, 2210.1 and 2210.2 for more information.

**Eye and Face Protection:**

Safety glasses with top and side shields or goggles. See Australian Standards AS/NZS 1336 and 1337 for more information.

(Contd. on page 4)

# SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.10.2013

Revision: 30.10.2013

**Product Name: MOTORKOTE DIESEL STICTION REMOVER**

(Contd. of page 3)

## 9 . PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:**

<b>Form:</b>	Liquid
<b>Colour:</b>	Green, green-blue
<b>Odour:</b>	Hydrocarbon
<b>Odour Threshold:</b>	Not determined.
<b>pH-Value:</b>	Not determined.
<b>Melting point/Melting range:</b>	Undetermined.
<b>Initial Boiling Point/Boiling Range:</b>	Undetermined.
<b>Flash Point:</b>	121.11 °C (ASTM D-93 PM Closed Cup)
<b>Flammability:</b>	Combustible liquid
<b>Auto-ignition Temperature:</b>	
<b>Decomposition Temperature:</b>	Not determined.
<b>Explosion Limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
<b>Vapour Pressure:</b>	Not determined.
<b>Relative Density at 25 °C:</b>	0.85 g/cm <sup>3</sup>
<b>Vapour Density at 20 °C:</b>	>1 g/cm <sup>3</sup>
<b>Evaporation Rate at 20 °C:</b>	<1 g/cm <sup>3</sup>
<b>Solubility in Water:</b>	Negligible
<b>Partition Coefficient (n-octanol/water):</b>	Not determined.
<b>Viscosity at 25 °C:</b>	70-125 cSt

## 10 . STABILITY AND REACTIVITY

**Possibility of Hazardous Reactions:** Hazardous polymerisation will not occur.**Chemical Stability:** Stable at ambient temperature and under normal conditions of use.**Conditions to Avoid:** Heat, sparks, open flames and other sources of ignition.**Incompatible Materials:** Strong oxidising agents.**Hazardous Decomposition Products:**

A complex mixture of airborne solid, liquid, particulates, and gases will evolve when this material undergoes pyrolysis or combustion.

## 11 . TOXICOLOGICAL INFORMATION

**Toxicity:****Acute Health Effects****Inhalation:** May cause nose, throat, and/or respiratory tract irritation.**Skin:**

May cause skin irritation. Skin absorption is possible but harmful effects are not expected under normal conditions of handling and use.

**Eye:** Causes serious eye irritation.**Ingestion:**

May cause gastrointestinal irritation with nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.**Serious Eye Damage / Irritation:** Causes serious eye irritation.

(Contd. on page 5)

# SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.10.2013

Revision: 30.10.2013

**Product Name: MOTORKOTE DIESEL STICTION REMOVER**

(Contd. of page 4)

**Respiratory or Skin Sensitisation:** No sensitising effects known.**Germ Cell Mutagenicity:** Not expected to be a hazard.**Carcinogenicity:**

Distillates (petroleum), solvent dewaxed heavy paraffinic is classified by Safe Work Australia as Carcinogen Category 2.

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3% DMSO extract as measured by IP 346. The manufacturers, distributors and importers of this substance shall be obliged to carry out an investigation to make themselves aware of the relevant and accessible data which exists for all other properties to classify and label the substance.

Residues (petroleum), atm. tower is classified by Safe Work Australia as Carcinogen Category 2.

**Reproductive Toxicity:** Not expected to be a hazard.**Specific Target Organ Toxicity (STOT) - Single Exposure:** Not expected to be a hazard.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:** Not expected to be a hazard.**Aspiration Hazard:** May be fatal if swallowed and enters airways.**Chronic Health Effects:**

Prolonged or repeated exposure may cause drying, redness, and cracking of the skin.

Prolonged or repeated exposure may cause moderate corneal injury and effects may be slow to heal.

**Existing Conditions Aggravated by Exposure:** Pre-existing skin and respiratory disorders.**12 . ECOLOGICAL INFORMATION****Ecotoxicity:** No information available**Aquatic toxicity:** No information available**Persistence and Degradability:** No information available**Bioaccumulative Potential:** No information available**Mobility in Soil:** No information available**13 . DISPOSAL CONSIDERATIONS****Disposal Methods and Containers:** Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

**14 . TRANSPORT INFORMATION****UN Number** Not applicable**ADG, IMDG, IATA** Void**Proper Shipping Name** Not applicable**ADG, IMDG, IATA** Void**Dangerous Goods Class** Not applicable**ADG Class:** Void**Packing Group:** Not applicable**ADG, IMDG, IATA** Void**Marine pollutant:** No

(Contd. on page 6)

# SAFETY DATA SHEET

According to Safe Work Australia

Printing date 30.10.2013

Revision: 30.10.2013

**Product Name: MOTORKOTE DIESEL STICTION REMOVER**

(Contd. of page 5)

## 15 . REGULATORY INFORMATION

**Australian Inventory of Chemical Substances:**

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

71-36-3 1-Butanol

**Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:**

Poisons Schedule: 5

## 16 . OTHER INFORMATION

**Creation Date:** 30.10.2013**Prepared by:** MSDS.COM.AU Pty Ltd[www.msds.com.au](http://www.msds.com.au)**Abbreviations and acronyms:**

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard

**Disclaimer**

This MSDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - December 2011"

The information contained in this material safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Verditure Trading Co. Pty Ltd makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.